

SPF 2000~5000TL HVM

- Integrated MPPT charge controller
- Configurable grid or solar input priority
- Optional WIFI/ GPRS remote monitoring
- Parallel for scalability



GROWATT

www.growatt.com

P O W E R
- I N G
T O M O R R O W

Datasheet	SPF 2000TL HVM-24	SPF 3000TL HVM-24	SPF 2000TL HVM-48	SPF 3000TL HVM-48	SPF 5000TL HVM/HVM-P
Battery voltage	24VDC		48VDC		
Battery type	Lithium/Lead-acid				
Inverter output					
Rated power	2000VA/ 2000W	3000VA/ 3000W	2000VA/ 2000W	3000VA/ 3000W	5000VA/ 5000W
Parallel capability	No				No/ Yes, 6 units maximum
AC voltage regulation (battery mode)	230VAC ± 5% @ 50/60Hz				
Surge power	4000VA	6000VA	4000VA	6000VA	10000VA
Efficiency (Peak)	93%				
Waveform	Pure sine wave				
Transfer time	10ms typical, 20ms Max				
Solar charger					
Maximum PV array power	1500W		1800W		4500W
MPPT range @ operating voltage	30VDC ~ 80VDC		60VDC ~ 115VDC		
Maximum PV array open circuit voltage	102VDC		145VDC		
Number of Independent MPP trackers/ strings per MPP tracker	1/1				
Maximum solar charge current	50A		30A		80A
Maximum efficiency	98%				
AC charger					
Charge current	30A		15A		60A
AC Input voltage	230 VAC				
Selectable voltage range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)				
Frequency range	50Hz/60Hz (Auto sensing)				
Physical					
Protection degree	IP20				
Dimension (W/H/D)	315/400/130mm				350/455/130mm
Net weight (kgs)	8	8.5	8	8.5	11.5
Operating environment					
Humidity	5% to 95% Relative Humidity(Non-condensing)				
Altitude	<2000m				
Operating temperature	0°C - 55°C				
Storage temperature	-15°C - 60°C				